

AD NO. 447
ASTIA FILE COPY

TECHNICAL REPORT NO. 6743

9 January 1952

FLIGHT TEST MEASUREMENT OF VERTICAL
AND HORIZONTAL TAIL LOADS DURING
RUDDER KICK AND STEADY SIDESLIP
MANEUVERS

D. W. Rhoads

Prepared by
Cornell Aeronautical Laboratory, Inc.
Buffalo, New York

United States Air Force
Air Research and Development Command
Wright Air Development Center
Wright-Patterson Air Force Base, Dayton, Ohio

FLIGHT TEST MEASUREMENT OF VERTICAL
AND HORIZONTAL TAIL LOADS DURING
RUDDER KICK AND STEADY SIDESLIP
MANEUVERS

D. W. Rhoads

United States Air Force
Air Research and Development Command
Wright Air Development Center
Wright-Patterson Air Force Base, Dayton, Ohio

ABSTRACT

The vertical and horizontal loads sustained during rudder kick and steady sideslip maneuvers have been investigated by means of flight tests conducted on an F-80A airplane by the Flight Research Department of the Cornell Aeronautical Laboratory, Inc., Buffalo, New York. The length of time the maximum rudder deflection is held has been shown to have a critical influence on the vertical tail load. Tests show that the most critical condition is reached if the rudder angle is forced to return to zero deflection from its maximum value at the time maximum heading change (~~or zero yaw rate~~) is attained.

The dissymmetry of the horizontal tail loads due to steady sideslip is illustrated by steady sideslip tests conducted for this purpose.

PUBLICATION REVIEW

Manuscript Copy of this report has been reviewed and found satisfactory for publication.

FOR THE COMMANDING GENERAL:

JACK A. GIBBS
Colonel, USAF
Chief, Aircraft Laboratory
Engineering Division

TABLE OF CONTENTS

	<u>Page No.</u>
FOREWORD	11
ABSTRACT	111
TABLE OF CONTENTS	iv
LIST OF FIGURES	v
SYMBOLS, DEFINITIONS AND CONVENTIONS	x
INTRODUCTION	1
EQUIPMENT AND METHODS	4
CONCLUSIONS AND RECOMMENDATIONS	6
REFERENCES	7
APPENDIX I	9
Dimensions and Leading Particulars	10
F-80A #44-85333 Photograph	13
F-80A Three View.	14
F-80A Mass Characteristics	15
Flight Conditions	16
Flight Log	17
Channel Sensitivities	23
F-80A Sign Convention	24
Flight Test Data	25

LIST OF FIGURES

<u>Figure No.</u>		<u>Page No.</u>
1	F-80A, Serial #44-85333, photograph	13
2	F-80A Three View	14
3	F-80A Sign Convention	24
4	Condition I: δ_r , r , FBM and FS Vs. Time	25
5	Condition I: β , Right and Left Stabilizer Shear, and Right and Left Bending Moment Vs. Time	26
6	Condition I: Δn_z , ϕ , δ_a and δ_e Vs. Time	27
7	Condition I: δ_r , r , FBM and FS Vs. Time	29
8	Condition I: β , Right and Left Stabilizer Shear, and Right and Left Bending Moment Vs. Time	30
9	Condition I: Δn_z , ϕ , δ_a and δ_e Vs. Time	31
10	Condition I: δ_r , r , FBM and FS Vs. Time	33
11	Condition I: β , Right and Left Stabilizer Shear, and Right and Left Bending Moment Vs. Time	34
12	Condition I: Δn_z , ϕ , δ_a and δ_e Vs. Time	35
13	Condition I: δ_r , r , FBM and FS Vs. Time	37
14	Condition I: β , Right and Left Stabilizer Shear, and Right and Left Bending Moment Vs. Time	38
15	Condition I: Δn_z , ϕ , δ_a and δ_e Vs. Time	39
16	Condition I: δ_r , r , FBM and FS Vs. Time	41
17	Condition I: β , Right and Left Stabilizer Shear and Right and Left Bending Moment Vs. Time	42
18	Condition I: Δn_z , ϕ , δ_a and δ_e Vs. Time	43
19	Condition IIa: δ_r , r , FBM and FS Vs. Time	45
20	Condition IIa: β , Right & Left Stabilizer Shear and Right and Left Bending Moment Vs. Time	46

LIST OF FIGURES - (continued)

<u>Figure No.</u>		<u>Page No.</u>
21	Condition IIa: Δh_z , p , δ_a and δ_e Vs. Time	47
22	Condition IIa: δ_n , r , FBM and FS Vs. Time	49
23	Condition IIa: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	50
24	Condition IIa: Δh_z , p , δ_a and δ_e Vs. Time	51
25	Condition IIb: δ_n , r , FBM and FS Vs. Time	53
26	Condition IIb: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	54
27	Condition IIb: Δh_z , p , δ_a and δ_e Vs. Time	55
28	Condition IIb: δ_n , r , FBM and FS Vs. Time	57
29	Condition IIb: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	58
30	Condition IIb: Δh_z , p , δ_a and δ_e Vs. Time	59
31	Condition III: δ_n , r , FBM and FS Vs. Time	61
32	Condition III: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	62
33	Condition III: Δh_z , p , δ_a and δ_e Vs. Time	63
34	Condition III: δ_n , r , FBM and FS Vs. Time	65
35	Condition III: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	66
36	Condition III: Δh_z , p , δ_a and δ_e Vs. Time	67
37	Condition III: δ_n , r , FBM and FS Vs. Time	69
38	Condition III: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	70
39	Condition III: Δh_z , p , δ_a and δ_e Vs. Time	71

LIST OF FIGURES - (continued)

<u>Figure No.</u>		<u>Page No.</u>
40	Condition IV: δ_n , n , FBM and FS Vs. Time	73
41	Condition IV: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	74
42	Condition IV: Δn_z , p , δ_a and δ_e Vs. Time	75
43	Condition IV: δ_n , n , FBM and FS Vs. Time	77
44	Condition IV: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	78
45	Condition IV: Δn_z , p , δ_a and δ_e Vs. Time	79
46	Condition V : δ_n , n , FBM and FS Vs. Time	81
47	Condition V : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	82
48	Condition V : Δn_z , p , δ_a and δ_e Vs. Time	83
49	Condition V : δ_n , n , FBM and FS Vs. Time	85
50	Condition V : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	86
51	Condition V : Δn_z , p , δ_a and δ_e Vs. Time	87
52	Condition V : δ_n , n , FBM and FS Vs. Time	89
53	Condition V : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	90
54	Condition V : Δn_z , p , δ_a and δ_e Vs. Time	91
55	Condition V : δ_n , n , FBM and FS Vs. Time	93
56	Condition V : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	94
57	Condition V : Δn_z , p , δ_a and δ_e Vs. Time	95
58	Condition VI: δ_n , n , FBM and FS Vs. Time	97

LIST OF FIGURES - (continued)

<u>Figure No.</u>		<u>Page No.</u>
59	Condition VI : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	98
60	Condition VI : Δh_z , p , δ_a and δ_e Vs. Time	99
61	Condition VI : δ_n , n , FBM and FS Vs. Time	101
62	Condition VI : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	102
63	Condition VI : Δh_z , p , δ_a and δ_e Vs. Time	103
64	Condition VI : δ_n , n , FBM and FS Vs. Time	105
65	Condition VI : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	106
66	Condition VI : Δh_z , p , δ_a and δ_e Vs. Time	107
67	Condition VI : δ_n , n , FBM and FS Vs. Time	109
68	Condition VI : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	110
69	Condition VI : Δh_z , p , δ_a and δ_e Vs. Time	111
70	Condition VII : δ_n , n , FBM and FS Vs. Time	113
71	Condition VII : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	114
72	Condition VII : Δh_z , p , δ_a and δ_e Vs. Time	115
73	Condition VII : δ_n , n , FBM and FS Vs. Time	117
74	Condition VII : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	118
75	Condition VII : Δh_z , p , δ_a and δ_e Vs. Time	119
76	Condition VIII : δ_n , n , FBM and FS Vs. Time	121
77	Condition VIII : β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	122


LIST OF FIGURES - (continued)

<u>Figure No.</u>		<u>Page No.</u>
78	Condition VIII: Δh_z , ϕ , δ_a and δ_e Vs. Time	123
79	Condition VIII: δ_n , n , FBM and FS Vs. Time	125
80	Condition VIII: β , Right and Left Stabilizer Shear and Right & Left Bending Moment Vs. Time	126
81	Condition VIII: Δh_z , ϕ , δ_a and δ_e Vs. Time	127
STEADY SIDESLIPS		
82	Condition IX: δ_n , δ_e and δ_a Vs. β	128
83	Condition IX: RS, LS, RBM, LBM, FS and FBM Vs. β	129
84	Condition X: δ_n , δ_e and δ_a Vs. β	130
85	Condition X: RS, LS, RBM, LBM, FS and FBM Vs. β	131
86	Condition XI: δ_n , δ_e and δ_a Vs. β	132
87	Condition XI: RS, LS, RBM, LBM, FS and FBM Vs. β	133

SYMBOLS, DEFINITIONS AND CONVENTIONS

Axes

Stability axes are used throughout this report. These mutually perpendicular axes are fixed to the airplane and, therefore, move with it during a maneuver. Their origin O lies at the center of gravity of the airplane. OX and OY lie in the plane of symmetry and OZ is perpendicular to it. These axes are fixed to the airplane by subjecting OX to the condition that it be parallel to the free stream wind vector in initial trimmed level flight.



- X Axis, or longitudinal axis is positive forward.
- Y Axis, or transverse axis is positive along the right wing.
- Z Axis, or normal axis is positive downward.

<u>MEASURED DATA</u>	<u>SYMBOL</u>	<u>POSITIVE DIRECTION</u>
1. Elevator Angle	δ_e	1. Trailing edge of elevator down.
2. Rudder Angle	δ_r or δ_r	2. Trailing edge of rudder to the left as you are looking along the positive X axis.
3. Total aileron angle	δ_a	3. Trailing edge of right aileron down (left wing down).
4. Normal acceleration	n_z	4. Acceleration of c.g. of the airplane in a downward direction (pilot is pushed against belt).
5. Right stabilizer bending moment	RBM	5. Moment due to load applied to a downward direction.
6. Left stabilizer bending moment	LBM	6. Moment due to load applied in a downward direction.
7. Right stabilizer shear	RS	7. Load applied in a downward direction.
8. Sideslip angle	β	8. Displacement along the y axis toward the right (nose to the left of relative wind).
9. Left stabilizer shear	LS	9. Load applied in a downward direction.
10. Fin bending moment	FBM	10. Moment due to load applied to the right looking along the positive X axis.
11. Fin shear	FS	11. Load applied to the right looking along positive X axis.
12. Rate of yaw	r	12. Angular velocity about the Z axis (clockwise when looking along + Z axis) (Nose to the right; right wing back).
13. Rate of roll	p	13. Angular velocity about the X axis to the right (right wing down).



INTRODUCTION

As a continuation of the dynamic stability and tail load study of the F-80A airplane, under Air Force Contract No. W33-038-ac-18517 (18480), this report presents the results of a series of rudder kick and sideslip flight tests in accordance with Change Order Number 13 of the above contract.


The primary objective of the rudder kick portion of the program was to determine the rudder deflection time history which would produce the most critical vertical tail loads, as well as to observe the relationship between the vertical tail load and the magnitudes of sideslip and rudder deflection applied. The tests were done at an altitude of 20,000' under several geometric and aerodynamic configurations, as noted below.

The purpose of the steady sideslip tests was to obtain data on the dissymmetry of the horizontal tail loads for future analysis. These tests were run at three different Mach numbers. A flight program block diagram appears below.

I. Rudder Kick




II. Steady Sideslip



The branches represent changes from the basic condition as indicated by the quantities in the branch boxes. A total of 26 rudder kick and 3 steady sideslip conditions is presented.

Theory


The assumption that the rudder kick maneuver may be critical from a vertical tail load standpoint may be illustrated in the following manner. If the rudder input is a step or the beginning of a ramp, the quantitative vertical tail response is:



Where $N_{VT} = f(\beta, \dot{\beta}, \ddot{\beta}, \delta_r)$

The rudder effectiveness contribution, $\left(\frac{\partial N_{VT}}{\partial \delta_r} \delta_r\right)$ is important for it

tends to, in the above case, reduce the tail load as indicated by the portion of the curve below the origin. If, however, the rudder is returned to its neutral position, in effect, a "reverse" step or partial ramp is produced as indicated below.



It may be seen that depending upon the timing of the return input (the combination with the initial input has now produced a full ramp input) the rudder effectiveness portion of the vertical tail load function is now added to that produced by the initial rudder motion. If rudder deflection magnitudes are excessive, the additional increment of tail load caused by the rudder effectiveness portion due to the return motion may produce a critical tail load.

F-80A vertical tail load flight test data obtained during previous programs was used to predict maximum vertical tail load during both the rudder kick and steady sideslip maneuver, thereby insuring the safety of pilot and test vehicle.

In addition to the basic load quantities recorded, control deflections, rotational velocities, normal acceleration and bending moments are presented as time histories.

EQUIPMENT AND METHODS

Equipment

The test vehicle used for these measurements was a Lockheed F-80A-IALO fighter type aircraft. This is a low wing, single place, jet propelled airplane powered by an Allison J-33-11 engine. Dimensions and leading particulars are on pages 10 through 12. A photograph and three view drawing are shown on pages 13 and 14.

Flight test data were recorded by a photo-observer and a fourteen channel Consolidated Engineering Corporation recording oscillograph.

The following items were recorded on the oscillograph:

1. Aileron Position
2. Elevator Position
3. Rudder Position
4. Normal Acceleration
5. Fin Shear
6. Fin Bending Moment
7. Sideslip Angle
8. Rolling Velocity
9. Yawing Velocity
10. Right Stabilizer Shear
11. Right Stabilizer Bending Moment
12. Left Stabilizer Shear
13. Left Stabilizer Bending Moment

Stabilizer shear and bending moment were measured at Station 10" from the stabilizer centerline. Fin shear and bending moment were measured at water line 129" from the reference centerline. Aileron, elevator, and rudder position were measured at the point where the control surfaces attach to the control system; that is, at the elevator and rudder horns and the aileron quadrants.

The following items were recorded on the photo-observer by a 35mm movie camera:

1. Airspeed (Ship's system and Prandtl tube)
2. Altitude
3. Outside Air Temperature
4. Fuel Quantity Remaining
5. Run Number (Oscillograph)
6. Frame Number (Camera)
7. Bank Angle
8. Stop Watch

For details of the recording instrumentation design procedures for calibration, and an estimate of overall recording accuracy, the reader is referred to Reference (1). The development of instrumentation for the purpose of measuring total tail loads and recording the data on a single oscillograph trace is presented in Reference (2). Details of instrumentation component types and models are recorded in Reference (3).

Methods

The condition imposed whereby the rudder kick duration is approximately one-half the Dutch roll period was designed to superimpose the return portion of the vertical tail load response on the peak of the load caused by the initial disturbance, thereby illustrating the maneuver characteristics which could cause a critical load condition. Previous flight has shown that, in response to a rudder step input, maximum sideslip angle (and, hence, vertical tail load) occurs at approximately zero yaw rate, which in turn approximates maximum heading angle. This latter quantity could be visualized by the pilot with reference to some point on the ground, and therefore used as a criterion for the specified program of kick durations.

Rudder kick maneuvers were performed both to the right and to the left. No particular difference may be noted between the two directions and no effort was made to present the same number of left and right for each condition. However, of the total number of rudder kick maneuvers presented, thirteen are to the left and thirteen are to the right.

Steady sideslips were performed for a number of rudder deflection magnitudes, ranging from approximately -8 to $+8$ degrees, resulting in sideslip, load and bending moments as a function of rudder deflection. An attempt to maintain zero rolling velocity was made by using sufficient aileron in each case to null the rolling moment due to sideslip velocity.

$\beta_{max} - \left(\frac{d\beta}{dt} = 0 \right) \text{ (approx } \psi)$
FVT (Approximate yawing rate)

CONCLUSIONS AND RECOMMENDATIONS

Examination of the flight test data obtained as a result of the continuation of this flight program has indicated the following:

1. The additional increment of tail load caused by the return of the rudder to its approximate neutral position is a considerable percentage of the load caused by the initial rudder displacement.
2. Whether or not this increment occurs at the maximum load due to the initial rudder disturbance depends on the rudder "holding time".
3. If the above does occur, the total load on the vertical tail may be critical, depending on the rudder magnitude initially adopted.
4. An extension of this maneuver to a "fishtail" maneuver, or a series of alternating positive and negative ramp inputs, indicates an even more critical condition due to the repeated alternating loads.
5. Sufficient data has been obtained during both the rudder kick and steady sideslip phases of this flight program to provide a fund of information for future analysis of this type of maneuver and to obtain a thorough check of the accuracy of any proposed method of calculation of these loads.

It is recommended that such analyses as noted above be carried out, including extension to more severe rudder kick maneuvers than performed during these flight tests.

REFERENCES

1. Kelly, D., Skelly, E. and Hirtreiter, W.J. "Instrumentation Of An F-80A Airplane For Dynamic Stability and Tail Load Flight Tests - Part I". Cornell Aeronautical Laboratory Report No. TB-495-F-8.
2. Walter, M.A. "Instrumentation of an F-80A Airplane for Dynamic Stability and Tail Load Flight Tests - Parts II and III". Cornell Aeronautical Laboratory Report No. TB-495-F-8.
3. Rhoads, D.W. "Flight Test Measurement of Vertical and Horizontal Tail Loads During a Rudder Locked Rolling Pullout Maneuver". Cornell Aeronautical Laboratory Report No. TB-541-F-4.
AFTR 6101

APPENDIX I

DIMENSIONS AND LEADING PARTICULARS

F-80A Serial No. 44-85333

I. <u>Principal Dimensions</u>	<u>Dimensions</u>
<u>A. Airplane - General</u>	
Span	33' 10-1/2"
Length (overall)	31' 6"
Height	11' 4"
<u>B. Wings</u>	
Airfoil Section	
Root	NACA 65 ₁ - 213 ($\mu = 0.6$)
Tip	NACA 65 ₁ - 213 ($\mu = 0.6$)
Chord at Root (at airplane $\frac{1}{4}$)	109.98"
Chord at Tip (Theoretical) (Tangent to tip)	41.99"
Incidence at Root	+ 1°
Incidence at Tip	-0° 30'
Dihedral - Trailing edge in Wing Ref. Plane	3° 50'
Sweepback (Leading edge)	0° 20'
Rear beam (Straight line) at	62% chord
Aspect Ratio	6.38
Taper Ratio (λ)	.381
Mean Aerodynamic Chord (MAC)	30.6"
Flap and aileron hinge ϕ at	76% chord
Leading edge of wing to leading edge of MAC	16.28"
<u>C. Empennage</u>	
Horizontal Stabilizer	
Airfoil Section NACA 65 ₁ 2 - 010	
Tail length (distance from 3/4 of wing MAC to elevator hinge line)	16.46 ft.
Tail length (distance from 3/4 of wing MAC to C/4 of tail MAC)	14.74 ft.
Span	15.60 ft.
Incidence to horizontal reference line	1° 30'
Root chord (C_R)	4.33 ft.
Tip chord (C_T)	1.503 ft.
Aspect ratio (AR)	6.56
Taper ratio (λ)	.388
Elevator E - ratio of elevator area to area of horizontal stabilizer (including elevator)	.246
Mean geometric elevator chord: c_e	
Elevator area: S_e	
$c_e S_e$	7.78 ft. ³

Trim tab dimensions	chord - 3 7/16"	span - 15.75"
Spring tab dimensions	chord - 4 5/8"	span - 10"
Elevator hinge center line at		75% chord

Vertical Stabilizer

Airfoil section	NACA 65 ₁ - 2 - 010
Height	7.92 ft.
Root chord (C _R)	5.41 ft.
Tip chord (C _T)	2.165 ft.
Aspect ratio (AR)	1.832
Taper ratio (λ)	.4
Rudder chord: (c _R)	
Rudder area: (S _R)	
c _R S _R	5.36 ft. ³
Trim Tab dimensions	chord - .75" span - 12"
Rudder hinge center line at	75% chord

D. Fuselage

Width (max.)	56"
Height (max.)	56"
Plan area	127.97 sq. ft.
Side area	135.86 sq. ft.
Distance from nose to 25% MAC	205.45"

II. Areas

	Sq. Ft.
A. Wing	
Total wing area	237.6
Wing flap area (total)	30.2
Total aileron area aft of hinge line (including tabs)	17.5
Left aileron trim tab area	0.4
B. Empennage	
Total Horizontal tail area	43.5
Stabilizer fixed area to elevator hinge (each)	17.4
Elevator area aft of hinge line (each) (including tabs)	4.35
Elevator trim tabs (each)	.47
Elevator spring tabs (each) -	.69
Total vertical tail area	22.5
Fin area	17.2
Rudder including fixed tab	5.3

III. Controls Surface Travel

	<u>up</u>	<u>down</u>
Ailerons	20°	20°
Aileron trim tabs (measured at inboard end of tab)	20°	20°
Elevators (measured at junction of inboard elevator rib and elevator tab hinge)	38°	16°
Elevator trim tabs	15°	15°
Tab servo ratio 1:3		
Elevator spring tabs	10°	22°
Wing flaps		45°
Dive recovery flaps		78°
Rudder (measured at bottom of rudder)	30° rt.	30° lt.

IV. Fuel Tanks Capacities

	<u>U.S. Gals.</u>
Fuselage (1)	207
Wing - Inboard forward (2)	60
Inboard aft (2)	70
Outboard intermediate (2)	22
Outboard (2)	8
Leading edge (2)	58
Tip (droppable) (2)	330
Total internal fuel capacity	425



F-80 A AIRPLANE 3/4 LEFT REAR VIEW

Figure 1




FIG. 2 BASIC DIMENSIONS OF F-60A AIRPLANE

F-80A MASS CHARACTERISTICS

The moments of inertia and gross weight of the airplane during these flight tests were approximately the same as for similar geometric configurations of Reference (3). For the tip tank off flights (c.g. at 30% MAC):

$$I_x \approx 7060 \text{ slug ft.}^2$$

$$I_z \approx 18000 \text{ slug ft.}^2$$

$$\text{Gross Weight} \approx 10,500 \text{ lbs.}$$

For the flights with empty tip tanks (same c.g.):

$$I_x \approx 9200 \text{ slug ft.}^2$$

$$I_z \approx 21500 \text{ slug ft.}^2$$

$$\text{Gross Weight} \approx 10,900 \text{ lbs.}$$

For the flights with half full tip tanks (same c.g.):

$$I_x \approx 21800 \text{ slug ft.}^2$$

$$I_z \approx 34500 \text{ slug ft.}^2$$

$$\text{Gross Weight} \approx 11,500 \text{ lbs.}$$

FLIGHT CONDITIONS

I. Rudder Kicks

Condition I

Alt. = 20,000 ft.

M.N. = .6

C.G. = 30% MAC

Clean Configuration

$T_1 \approx 1/2$ Dutch roll period ≈ 1 sec.

$\Delta T_1 = \Delta T_2 = .2$ sec.

$\delta_{R_{MAX}}$ ranges from 2 to 5 degrees

Condition IIa

Same as Condition I except $T_1 < 1/2$ Dutch roll period $\approx .5$ sec.

$\delta_{R_{MAX}} \approx 3$ and 4 degrees

Condition IIb

Same as Condition I except $T_1 > 1/2$ Dutch roll period ≈ 1.5 sec.

$\delta_{R_{MAX}} \approx 3$ and 4 degrees

Condition III

Same as Condition I except $\Delta T_1 = \Delta T_2$ is varied from .1 sec.

to .5 sec. $\delta_{R_{MAX}} \approx 3, 3.5$ and 4 degrees

Condition IV

Same as Condition I except that M.N. = .4 $\delta_{R_{MAX}} \approx 4$ degrees

Condition V

Same as Condition I except that M.N. = .7 $\delta_{R_{MAX}} \approx 2, 3,$ and 4 degrees

Condition VI

Same as Condition I except empty tip tanks. $\delta_{R_{MAX}} \approx 3, 3.5$ and 4.5 degrees.

Condition VII

Same as Condition I except half full tip tanks. $\delta_{R_{MAX}} \approx 3.5$ and 4 degrees.

Condition VIII

Same as Condition I except ailerons are manually moved to prevent rolling. $\delta_{R_{MAX}} \approx 3, 4$ and 5 degrees.

II. Steady Sideslip

Condition IX - Altitude = 20,000 ft.

M.N. = .4

C.G. = 30%

Clean Configuration

Condition X - Same as Condition IX except M.N. = .6

Condition XI - Same as Condition IX except M.N. = .7

FLIGHT LOG

F-80A RUDDER KICK FLIGHT TEST PROGRAM
F-80A #44-85333

FLT. NO.	DATE	PURPOSE	DATA REQUESTED										DATA OBTAINED										COMMENTS	
			MACH	δ_N	*	δ_a	T_1	ΔT_1	ΔT_2	TIP TANKS	RUN	COND.	MACH	δ_N	*	δ_a	T_1	ΔT_1	ΔT_2	TIP TANKS				
33	7/20	Cond. I, IIa, IIb, III, IV, V	.4	40	R	Locked	1	.2	.2	Off	9138	IV	.39	-3.80	R	Locked	1.5	.2	.2	Off	Reduced			
			.4	40	R	"	1	.2	.2	Off	9139	I	.60	-3.00	R	Locked	1.25	.2	.2	Off	Good run, not read.			
			.6	40	R	"	1	.2	.2	Off	9140	I									Off	Reduced.		
			.6	40	R	"	1	.2	.2	Off	9141											Off	Good run, not read.	
			.6	40	R	"	1.5	.2	.2	Off	9142	IIb	.59	-3.20	R	Locked	1.75	.2	.2	.2	Off	Good run, not read.		
			.6	40	R	"	1.5	.2	.2	Off	9143	IIa	.59	-3.00	R	Locked	.75	.2	.2	.2	Off	Reduced		
			.6	40	R	"	.5	.2	.2	Off	9144											Off	Reduced	
			.6	40	R	"	.5	.2	.2	Off	9145												Off	Good run, not read.
			.6	40	R	"	1	.1	.1	Off	9146	III	.59	-3.60	R	Locked	1.00	.1	.1	.1	Off	Good run, not read.		
			.6	40	R	"	1	.1	.1	Off	9147	III										Off	Good run, not read.	
			.6	40	R	"	1	.5	.5	Off	9148	III										Off	Reduced	
			.6	40	R	"	1	.5	.5	Off	9149	III										Off	$\Delta T_1, \Delta T_2, T_1$ do not conform to req. conditions.	
			.6	20	R	"	1	.2	.2	Off	9150											Off	"	
			.6	20	R	"	1	.2	.2	Off	9151	I	.60	-2.30	R	Locked	1.2	.2	.2	.2	Off	Good run, not read.		
			.7	20	R	"	1	.2	.2	Off	9152											Off	Reduced.	
.7	20	R	"	1	.2	.2	Off	9153											Off	Good run, not read.				
.7	20	R	"	1	.2	.2	Off	9154	V	.69	-2.30	R	Locked	1.2	.2	.2	.2	Off	Good run, not read.					

* Direction

FLIGHT LOG

F-80A RUDDER KICK FLIGHT TEST PROGRAM
F-80A #44-85333

FLT. NO.	DATE 1951	PURPOSE	DATA REQUESTED										COMMENTS											
			MACH	δ_n	*	δ_a	T	ΔT	ΔI_2	TIP TANKS	RUN	COND.		MACH	δ_n	*	δ_a	T	ΔT	ΔI_2	TIP TANKS			
34	7/23	Cond. I, IIa, IIb, IV, V	.4	4°	L	Locked	1	.2	.2	.2	Off	9206	IV	.39	5°	L	Locked	1.5	.2	.2	Off	Reduced.		
			.4	4°	L	"	1	.2	.2	.2	Off	9207	I	.59	3.9°	L	Locked	1.3	.2	.2	Off	Good run, not read.		
			.6	4°	L	"	1	.2	.2	.2	Off	9208	I										Reduced.	
			.6	4°	L	"	1	.2	.2	.2	Off	9209	I											Good run, short steady state.
			.6	4°	L	"	2	.2	.2	.2	Off	9210	IIb	.56	4.3°	L	Locked	1.9	.2	.2	.2	Off	Reduced.	
			.6	4°	L	"	2	.2	.2	.2	Off	9211	I											Good run, not read.
			.6	4°	L	"	3	.2	.2	.2	Off	9212	I											Good run, not read.
			.6	4°	L	"	3	.2	.2	.2	Off	9213	IIa	.58	4.2°	L	Locked	.8	.2	.2	.2	Off	Reduced	
			.6	4°	L	"	1	.1	.1	.1	Off	9214	I	.58	4.8°	L	Locked	1.2	.2	.1	.1	Off	Good run, not read.	
			.6	4°	L	"	1	.1	.1	.1	Off	9215	I										Reduced.	
			.6	4°	L	"	1	.5	.5	.5	Off	9216	I											T, ΔT , ΔI_2 do not conform to required conditions.
			.6	4°	L	"	1	.5	.5	.5	Off	9217	I	.59	2.5°	L	Locked	1.2	.2	.25	.25	Off	"	
			.6	2°	L	"	1	.2	.2	.2	Off	9218	I											Reduced.
			.6	2°	L	"	1	.2	.2	.2	Off	9219	I											Good run, not read.
			.7	2°	L	"	1	.2	.2	.2	Off	9220	V	.69	2.6°	L	Locked	1.1	.2	.2	.2	Off	Reduced.	
			.7	2°	L	"	1	.2	.2	.2	Off	9221	I											Good run, not read.
			.7	2°	L	"	1	.2	.2	.2	Off	9222	I											Good run, not read.
			.7	2°	L	"	1	.2	.2	.2	Off	9223	I											Good run, not read.

* Direction

FLIGHT LOG

F-80A RUDDER KICK FLIGHT TEST PROGRAM
F-80A #44-85333

FLT. NO.	DATE 1951	PURPOSE	DATA REQUESTED				DATA OBTAINED							COMMENTS				
			MACH	δ_r	* δ_a	T	ΔT	ΔZ	TIP TANKS	RUN	COND.	MACH	δ_r		* δ_a	T	ΔT	ΔZ
35	7/24	Cond. V VIII	.6	4°	R	1	.5	.5	Off	9307			Locked	1.1	.48	.2	Off	T, ΔT , ΔZ do not conform to required conditions.
			.6	4°	R	1	.5	.5	Off	9308			Locked	.9	.48	.2	Off	"
			.6	4°	R	1	.5	.5	Off	9309			Locked	.9	.2	.2	Off	"
			.6	4°	R	1	.2	.2	Off	9310			Moved anti-roll	Not Reduced				Movement of ailerons did not improve roll rate.
			.6	4°	R	1	.2	.2	Off	9311			"	"	"			"
			.7	4°	R	1	.2	.2	Off	9312			Locked	1.0	.2	.2	Off	Reduced, not present ed.
			.7	4°	R	1	.2	.2	Off	9313	V		Locked	.9	.2	.1	Off	Reduced.
			.6	4°	L	1	.5	.5	Off	9314			Locked	.9	.1	.15	Off	T, ΔT , ΔZ do not conform to required conditions.
			.6	4°	L	1	.5	.5	Off	9315			Locked	.9	.3	.2	Off	"
			.6	4°	L	1	.5	.5	Off	9316			Locked	.9	.25	.2	Off	"
			.6	4°	L	1	.2	.2	Off	9317	VIII		Moved anti-roll	1.0	.2	.1	Off	Reduced. (Roll rate not minimized).
			.6	1°	L	1	.2	.2	Off	9318			"					Good run, not read.
			.7	4°	L	1	.2	.2	Off	9319			Locked					(Roll rate not minimized).
			.7	4°	L	1	.2	.2	Off	9320	V		Locked	1.0	.2	.2	Off	Good run, not read.
			.7	4°	L	1	.2	.2	Off	9321			Locked					Reduced.
			.4	2°	L	1	.2	.2	Off	9322	IX		Not reduced. Repeated. #36 with sensitivities changed.					Good run, not read.
			.4	2°	R	1	.2	.2	Off	9323	IX		"					On edge of paper.
			.4	4°	R	1	.2	.2	Off	9324	IX		"					Off paper.
			.4	4°	R	1	.2	.2	Off	9325	IX		"					
			.4	6°	L	1	.2	.2	Off	9326	IX		"					
			.4	6°	R	1	.2	.2	Off	9327	IX		"					
			.4	8°	R	1	.2	.2	Off	9328	IX		"					
			.4	8°	R	1	.2	.2	Off	9329	IX		"					
			.4	10°	L	1	.2	.2	Off	9330	IX		"					Off paper.

#Direction

FLIGHT LOG

F-80A RUDDER KICK FLIGHT TEST PROGRAM
F-80A #44-85333

FLI. NO.	DATE 1951	PURPOSE	DATA REQUESTED				DATA OBTAINED				COMMENTS					
			MACH	δ_a	T	$\Delta T, \Delta T_2$	TIP TANKS	RUN COND.	MACH	δ_a		T	$\Delta T, \Delta T_2$	TIP TANKS		
36	7/25	Cond. III, IX, X, XI	.4	R			Off	IX	.4				Off	Reduced		
			.4	R			Off	IX	.4				Off	Reduced		
			.4	R			Off	IX	.4				Off	Reduced		
			.4	R			Off	IX	.4				Off	Reduced		
			.4	R			Off	IX	.4				Off	Reduced		
			.4	R			Off	IX	.4				Off	Reduced		
			.6	R			Off	X	.58				Off	Reduced		
			.6	R			Off	X	.58				Off	Reduced		
			.6	R			Off	X	.58				Off	Reduced		
			.6	R			Off	X	.58				Off	Reduced		
			.6	R			Off	X	.58				Off	Reduced		
			.6	R			Off	X	.58				Off	Reduced		
			.7	R			Off	X	.69				Off	Reduced		
			.7	R			Off	XI	.69				Off	Reduced		
			.7	R			Off	XI	.69				Off	Reduced		
			.7	R			Off	XI	.69				Off	Reduced		
			.7	R			Off	XI	.69				Off	Reduced		
			.7	R			Off	XI	.69				Off	Reduced		
			.6	R			1 Locked	III	.5		-3.2°	R Locked	1.0	.3	.5	Reduced
			.6	R			1 Locked		.5							Bad run, too long.
.6	R			1 Locked		.5							"			
.6	R			1 Locked		.5							"			
.6	R			1 Moved		.2							Bad run, pilot unable to keep out roll.			
.6	R			Anti-roll		.2							"			
.6	R			"		.2							"			
.6	R			"		.2							"			
.6	R			"		.2							"			

* Direction

FLIGHT LOG

F-80A RUDDER KICK FLIGHT TEST PROGRAM
F-80A #44-85333

FLT. NO.	DATE 1951	PURPOSE	DATA REQUESTED				DATA OBTAINED				COMMENTS							
			MACH	δ_r	* δ_a	T, ΔT , ΔT_2	TIP TANKS	RUN	COND.	MACH		δ_r	* δ_a	T, ΔT , ΔT_2	TIP TANKS			
37	7/26	Cond. III, VIII, IX, XI	.4	0°	L	Off	IX	.39					Off	Reduced				
			.4	20°	L	Off	IX	.39						Off	Reduced			
			.4	40°	L	Off	IX	.39							Off	Reduced		
			.4	60°	L	Off	IX	.39							Off	Reduced		
			.4	80°	L	Off	IX	.39							Off	Reduced		
			.4	100°	L	Off	IX	.39							Off	Reduced		
			.6	0°	L	Off	X	.59							Off	Reduced		
			.6	20°	L	Off	X	.59							Off	Reduced		
			.6	40°	L	Off	X	.59							Off	Reduced		
			.6	60°	L	Off	X	.59							Off	Reduced		
			.6	80°	L	Off	X	.59							Off	Reduced		
			.6	100°	L	Off	X	.59							Off	Reduced		
			.7	0°	L	Off	XI	.69							Off	Reduced		
			.7	20°	L	Off	XI	.69							Off	Reduced		
			.7	40°	L	Off	XI	.69							Off	Reduced		
			.7	60°	L	Off	XI	.69							Off	Reduced		
			.7	80°	L	Off	XI	.69							Off	Reduced		
			.7	100°	L	Off	XI	.69							Off	Reduced		
			.6	0°	L	Off	X	.59							Off	Reduced		
			.6	40°	L	Locked	1	.5	III	.59	4°	L	Locked	1.3	.4	.5	Off	Good run, not read.
			.6	40°	L	Locked	1	.5	III	.59							Off	Reduced
			.6	40°	L	Locked	1	.5	III	.59							Off	Good run, not read.
			.6	40°	L	Locked	1	.5	III	.59							Off	Good run, not read.
			.6	40°	L	Locked	1	.5	III	.59							Off	Good run, not read.
			.6	40°	L	Moved	1	.2	VIII	.59							Off	Good run, not read.
			.6	40°	L	anti-roll	1	.2	VIII	.59	5°	L	Moved anti-roll	1.2	.2	.2	Off	Reduced, unable to prevent roll.
.6	40°	L	roll	1	.2	VIII	.59							Off	Reduced, unable to prevent roll.			
.6	40°	L	"	1	.2	VIII	.59							Off	Good run, not read.			
.6	40°	L	"	1	.2	VIII	.59							Off	Good run, not read.			
.6	40°	L	"	1	.2	VIII	.59							Off	Good run, not read.			
.6	40°	L	"	1	.2	VIII	.59							Off	Good run, not read.			

* Direction

FLIGHT LOG

F-80A RUDDER KICK FLIGHT TEST PROGRAM
F-80A #44-85333

FLT. NO.	DATE 1951	PURPOSE	DATA REQUESTED					DATA OBTAINED					COMMENTS								
			MACH	δ_e	#	δ_a	T	ΔT	ΔT_2	TIP TANKS	RUN	COND.		MACH	δ_e	#	δ_a	T	ΔT	ΔT_2	TIP TANKS
38	8/2	Cond. VI VII	.6	4°	R	Locked	1	.2	.2	Half full	9734	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Good run, not read.
			.6	4°	R	"	1	.2	.2	"	9735	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Reduced
			.6	4°	R	"	1	.2	.2	"	9736	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Good run, not read.
			.6	4°	L	"	1	.2	.2	"	9737	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Good run, not read.
			.6	4°	L	"	1	.2	.2	"	9738	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Good run, not read.
			.6	4°	L	"	1	.2	.2	"	9739	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Reduced
			.6	4°	L	"	1	.2	.2	"	9740	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Good run, not read.
			.6	4°	L	"	1	.2	.2	Empty	9741	VII	.58	-3.5°	R	Locked	1.3	.2	.1	Half full	Good run, not read.
			.6	4°	L	"	1	.2	.2	Empty	9742	VI	.59	4.6°	L	Locked	1.1	.2	.2	Empty	Good run, not read.
			.6	4°	R	"	1	.2	.2	"	9743	VI	.59	4.6°	L	Locked	1.1	.2	.2	Empty	Reduced
			.6	4°	R	"	1	.2	.2	"	9744	VI	.59	-3°	R	Locked	1.1	.2	.2	"	Good run, not read.
			.6	4°	R	"	1	.2	.2	"	9745	VI	.59	-3°	R	Locked	1.1	.2	.2	"	Reduced
			.6	4°	R	"	.5	.2	.2	"	9746	VI	.59	-3.4°	R	Locked	.8	.2	.1	"	Good run, not read.
			.6	4°	R	"	.5	.2	.2	"	9747	VI	.59	-3.4°	R	Locked	.8	.2	.1	"	Good run, not read.
			.6	4°	R	"	1.5	.2	.2	"	9748	VI	.59	-3.4°	R	Locked	1.5	.2	.2	"	Reduced
.6	4°	R	"	1.5	.2	.2	"	9749	VI	.59	-3.4°	R	Locked	1.5	.2	.2	"	Reduced			
.6	0°	R	"				"	9750	X	.60										Good run, not read.	
.6	2°	R	"				"	9751	X	.60											Reduced
.6	4°	R	"				"	9752	X	.60											Reduced
.6	4.5°	R	"				"	9753	X	.60											Reduced

* Direction

CHANNEL SENSITIVITIES

Channel	Date	Sensitivity	Effective Flights
Rudder Angle	7/9/51	1.796°/in.	32-38
Yaw Rate	7/16/51	2.61°/sec/in.	32, 33
	7/16/51	3.99°/sec/in.	34, 35
	8/1/51	4.08°/sec/in.	36-38
Fin Shear	7/13/51	825#/in.	32, 33
		803#/in.	34
		808#/in.	35, 36
		820#/in.	37
		810#/in.	38
Fin Bending Moment	7/13/51	16,650 in.#/in.	32, 33
		15,534 in.#/in.	34
		15,686 in.#/in.	35, 36
		16,560 in.#/in.	37
		16,110 in.#/in.	38
Normal Acceleration	5/15/51	1.935 g/in.	32-38
Roll Rate	7/16/51	12.75°/sec/in.	32-35
	7/26/51	12.31°/sec/in.	36-38
Aileron Deflection	7/16/51	4.57°/in.	32-38
Elevator Deflection	6/28/51	2.45°/in.	32-38
Sideslip Angle	6/28/51	11.42 in H ₂ O/in.	32-38
Right Stabilizer Shear	7/11/51	303#/in.	32-34
	7/24/51	312#/in.	35-38
Left Stabilizer Shear	7/11/51	338#/in.	32-34
	7/24/51	351#/in.	35-38
Right Stabilizer Bending Moment	7/11/51	14,350 in.#/in.	32-34
	7/24/51	13,500 in.#/in.	35-38
Left Stabilizer Bending Moment	7/11/51	13,700 in.#/in.	32-34
	7/24/51	12,800 in.#/in.	35-38

F-80A SIGN CONVENTION
ARROWS SHOW POSITIVE QUANTITIES




Figure 3

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.9%
 KICK DURATION T_1 1.3 SEC.
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .3 SEC
 AILERON *LOCKED*
 CONDITION I

FLIGHT 34
 RUN 9208
 TIP TANKS OFF
 ALTITUDE 27,920 FT.
 O.A.T. -13.0°C
 V_0 303.2 MPH
 PE




Figure 4

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 34

RUDDER δ_r 3.9%

RUN 9208

KICK DURATION T_1 1.3 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,194 FT.

TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -130 °C

AILERON LOCKED

V_0 303.2 MPH




Figure 5

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.5%
 KICK DURATION T_1 .15 SEC.
 TIME TO APPLY ΔT_1 .1 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9208
 TIP TANKS OFF
 ALTITUDE 20,194 FT.
 O.A.T. -130 °C
 V_0 3035 MPH

CONDITION I




Figure 6

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .58
 RUDDER δ_R 4.8°
 KICK DURATION T_1 .12 SEC
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .1 SEC
 AILERON LOCKED

FLIGHT 34
 RUN 9215
 TIP TANKS OFF
 ALTITUDE 20,035 FT
 O.A.T. -13.0°
 V_0 296.5 MPH

CONDITION I




Figure 7

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .50

FLIGHT 34

RUDDER δ_R 4.8°

RUN 9215

KICK DURATION T_1 1.2 SEC

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC




ALTITUDE 20,035 FT.

TIME TO RETURN ΔT_2 .1 SEC

O.A.T. -130 °C

AILERON LOCKED

V_0 298.5 MPH



t - SEC.

Figure 8

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER *58*
 RUDDER δ_R *4.8^\circ*
 KICK DURATION T_1 *1.2 SEC.*
 TIME TO APPLY ΔT_1 *.2 SEC.*
 TIME TO RETURN ΔT_2 *.1 SEC.*
 AILERON *LOCKED*

FLIGHT *34*
 RUN *9215*
 TIP TANKS *OFF*
 ALTITUDE *20,035 FT*
 O.A.T. *-13.0 °C*
 V_0 *298.5 MPH*

CONDITION I




Figure 9

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 2.5°
 KICK DURATION T_1 1.9 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9218
 TIP TANKS OFF
 ALTITUDE 20,000 FT.
 O.A.T. 12.7°
 V_0 308.9 MPH

CONDITION I





Figure 10

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 2.5°
 KICK DURATION T_1 1.4 SEC
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC
 AILERON LOCKED

FLIGHT 34
 RUN 9218
 TIP TANKS OFF
 ALTITUDE 20018 FT.
 O.A.T. -12.7°C
 V_0 302.9 MPH



t - SEC.
 Figure 11

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

RUDDER δ_R 2.5%

KICK DURATION T_1 1.4 SEC.

TIME TO APPLY ΔT_1 .25 SEC

TIME TO RETURN ΔT_2 .25 SEC

AILERON LOCKED

FLIGHT 34

RUN 9218

TIP TANKS OFF

ALTITUDE 20,000 FT

O.A.T. -12.7 C

V_0 302.9 MPH

CONDITION I




Figure 12

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .60
 RUDDER δ_R 3.0°R
 KICK DURATION T_1 1.25 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9140
 TIP TANKS OFF
 ALTITUDE 20200 FT.
 O.A.T. -17.4°C
 V_0 307.1 MPH

CONDITION I




Figure 13

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .6
 RUDDER δ_R 3.0°R
 KICK DURATION T_1 1.25 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 3140
 TIP TANKS OFF
 ALTITUDE 20,200 FT
 O.A.T. -17.4°C
 V_0 307.1 MPH




Figure 14

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .6
 RUDDER δ_R 3.0°
 KICK DURATION T_1 1.25 SEC.
 TIME TO APPLY ΔT_1 2 SEC.
 TIME TO RETURN ΔT_2 2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9140
 TIP TANKS OFF
 ALTITUDE 20,200 FT
 O.A.T. -17.4°C
 V_0 307.1 MPH

CONDITION I




Figure 15

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .50
 RUDDER δ_R 5 DEG
 KICK DURATION T_1 .2 SEC
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC
 AILERON 100000

FLIGHT 33
 RUN 9151
 TIP TANKS OFF
 ALTITUDE 20,110 FT
 O.A.T. -17.5°C
 V_0 306.8 MPH

CONDITION I

ON







Figure 16

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .60
 RUDDER δ_R 2.3°
 KICK DURATION T_1 1.2 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9151
 TIP TANKS OFF
 ALTITUDE 20,110 FT.
 O.A.T. -17.4°C
 V_0 306.4 MPH



1 - SEC.
 Figure 17

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .60

FLIGHT 33

RUDDER δ_R 2.3°R

RUN 9131

KICK DURATION T_1 1.2 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,110 FT.

TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -17.4 °C

AILERON LOCKED

V_0 306.4 MPH.

CONDITION I




Figure 18

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .58
 RUDDER δ_R 4.2°
 KICK DURATION T_1 .8 SEC
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC
 AILERON LOCKED
 CONDITION J-2

FLIGHT 34
 RUN 9213
 TIP TANKS OFF
 ALTITUDE 20,144 FT.
 O.A.T. -12.7°C
 V_0 298.7 MPH




Figure 19

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .58

FLIGHT 34

RUDDER δ_R 4.2°

RUN 9213

KICK DURATION T_1 .8 SEC

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,144 FT.



TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -12.7°C


AILERON LOCKED

V_0 298.7 MPH

CONDITION II-2



— R-SHEAR
- - - L-SHEAR



— R-BM
- - - L-BM

↑ - SEC.

Figure 20

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .58
 RUDDER δ_r 4.2°
 KICK DURATION T_1 .8 SEC.
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9213
 TIP TANKS OFF
 ALTITUDE 20,100 FT.
 O.A.T. -12.7 °C
 V_0 298.7 MPH

CONDITION II-a




Figure 21

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.0°R
 KICK DURATION T_1 .75 SEC.
 TIME TO APPLY ΔT_1 .1 SEC
 TIME TO RETURN ΔT_2 .2 SEC
 AILERON LOCKED

FLIGHT 33
 RUN 9144
 TIP TANKS OFF
 ALTITUDE 20,500 FT.
 O. A. T. -18.3 °C
 V_0 308.9 MPH

CONDITION Γ -2

δ_R

$\dot{\alpha}$

FBM
FS




Figure 22

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R $3.0^\circ R$
 KICK DURATION T_1 .75 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9144
 TIP TANKS OFF
 ALTITUDE 29500 FT.
 O.A.T. $-18.3^\circ C$
 V_0 303.9 MPH




Figure 23

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 30°R
 KICK DURATION T_1 .75 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9144
 TIP TANKS OFF
 ALTITUDE 20,500 FT.
 O.A.T. -18.3 °C
 V_0 303.9 MPH

CONDITION II-a.




Figure 24

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .56
 RUDDER δ_r 4.3%
 KICK DURATION T_1 1.9 SEC.
 TIME TO APPLY ΔT_1 2 SEC.
 TIME TO RETURN ΔT_2 2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9210
 TIP TANKS OFF
 ALTITUDE 20,058 FT.
 O. A. T. -12.5°C
 V_0 299.8 MPH

CONDITION II-b





Figure 25

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .56
 RUDDER δ_R 4.3%
 KICK DURATION T_1 1.9 SEC.
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9210
 TIP TANKS OFF
 ALTITUDE 20,050 FT.
 O.A.T. -12.5°C
 V_0 299.8 MPH



t - SEC.

Figure 26

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .86
 RUDDER δ_R 4.3°
 KICK DURATION T_1 1.9 SEC
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9210
 TIP TANKS OFF
 ALTITUDE 20,050 FT.
 O.A.T. -12.5°C
 V_0 299.8 MPH

CONDITION II-b





Figure 27

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
RUDDER δ_R 3.2°
KICK DURATION T_1 1.75 SEC.
TIME TO APPLY ΔT_1 .2 SEC.
TIME TO RETURN ΔT_2 .2 SEC.
AILERON LOCKED

FLIGHT 33
RUN 9143
TIP TANKS OFF
ALTITUDE 20,530 FT
O.A.T. -13.4 °C
 V_0 301.2 MPH.

CONDITION II-b



F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 33

RUDDER δ_R 3.2°R

RUN 9143

KICK DURATION T_1 1.75 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,530 FT.

TIME TO RETURN ΔT_2 .2 SEC.

O. A. T. -18.4°C

AILERON LOCKED

V_0 301.2 MPH.

CONDITION II-b




Figure 29

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.2° R
 KICK DURATION T_1 1.75 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9143
 TIP TANKS OFF
 ALTITUDE 20,530 FT.
 O. A. T. -18.4°C
 V_0 301.2 MPH

CONDITION II-b




Figure 30

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 37

RUDDER δ_R 4°

RUN 9684

KICK DURATION T_1 1.5 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .4 SEC.

ALTITUDE 29,125 FT.

TIME TO RETURN ΔT_2 .5 SEC.

O.A.T. -11.3°C

AILERON LOCKED

V_0 302 MPH

CONDITION III




Figure 31

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 37

RUDDER δ_R 4°

RUN 9684

KICK DURATION T_1 1.3 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .4 SEC.

ALTITUDE 20,125 FT.




TIME TO RETURN ΔT_2 .5 SEC.

O.A.T. -11.3 °C

AILERON LOCKED

V_0 308 MPH

CONDITION III



t - SEC.

Figure 32

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 37

RUDDER δ_R 4°

RUN 9684

KICK DURATION T_1 1.3 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .4 SEC.

ALTITUDE 20,125 FT.

TIME TO RETURN ΔT_2 .5 SEC.

O.A.T. -11.3°C

AILERON LOCKED

V_0 302 MPH

CONDITION III




Figure 33

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 36

RUDDER δ_r 3.2°E

RUN 9424

KICK DURATION T_1 10 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .3 SEC.

ALTITUDE 29 227 FT.

TIME TO RETURN ΔT_2 .5 SEC.

O.A.T. -11.5°C

AILERON LOCKED

V_0 301 MPH

CONDITION III




Figure 34

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 36

RUDDER δ_R 3.2°

RUN 9424

KICK DURATION T_1 1.0 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .3 SEC.

ALTITUDE 20,227 FT.



TIME TO RETURN ΔT_2 .5 SEC.

O.A.T. -11.5°C


AILERON LOCKED

V_0 301 MPH

CONDITION III



— RS
- - - LS



— RBM
- - - LBM

t - SEC.

Figure 35

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.2°R
 KICK DURATION T_1 1.0 SEC.
 TIME TO APPLY ΔT_1 .3 SEC.
 TIME TO RETURN ΔT_2 .5 SEC.
 AILERON LOCKED

FLIGHT 36
 RUN 9424
 TIP TANKS OFF
 ALTITUDE 20,227 FT.
 O.A.T. -11.5°C
 V_0 301 MPH

CONDITION III




Figure 36

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.6°R
 KICK DURATION T_1 1.00 SEC
 TIME TO APPLY ΔT_1 .1 SEC
 TIME TO RETURN ΔT_2 .1 SEC
 AILERON LOCKED

FLIGHT 33
 RUN 9147
 TIP TANKS OFF
 ALTITUDE 20,500 FT.
 O.A.T. -18.3 °C
 V_0 302.6 MPH.

CONDITION III




Figure 37

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.6°
 KICK DURATION T_1 1.00 SEC.
 TIME TO APPLY ΔT_1 .1 SEC.
 TIME TO RETURN ΔT_2 .1 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9147
 TIP TANKS OFF
 ALTITUDE 20,500 FT.
 O. A. T. -16.3°C
 V_0 302.6 MPH




Figure 38
- 70 -

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 36°
 KICK DURATION T_1 1.00 SEC.
 TIME TO APPLY ΔT_1 .1 SEC.
 TIME TO RETURN ΔT_2 .1 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9147
 TIP TANKS OFF
 ALTITUDE 20,500 FT.
 O. A. T. -18.3 °C
 V_0 302.6 MPH

CONDITION III




Figure 39

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .39

FLIGHT 34

RUDDER δ_R 5%

RUN 9206

KICK DURATION T_1 1.5 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,084 FT.


TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -14.0 °C

AILERON LOCKED

V_0 203.5 MPH.

CONDITION IV



t - SEC.

Figure 40

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 5%
 KICK DURATION T_1 1.5 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9206
 TIP TANKS OFF
 ALTITUDE 20,000 FT
 O.A.T. -14.0 °C
 V_0 203.5 MPH






Figure 41
- 74 -

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .89

RUDDER δ_R 5%

KICK DURATION T_1 1.5 SEC.

TIME TO APPLY ΔT_1 .2 SEC.

TIME TO RETURN ΔT_2 .2 SEC.

AILERON LOCKED

FLIGHT 34

RUN 9206

TIP TANKS OFF

ALTITUDE 20,000 FT

O.A.T. -14.0 °C.

V_0 203.5 MPH

CONDITION IV




Figure 12

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .39
 RUDDER δ_R 3.8° R
 KICK DURATION T_1 1.5 Sec.
 TIME TO APPLY ΔT_1 .2 Sec
 TIME TO RETURN ΔT_2 .2 Sec
 AILERON LOCKED

FLIGHT 33
 RUN 9/38
 TIP TANKS OFF
 ALTITUDE 20,210 FT.
 O.A.T. -17.4 °C
 V_0 201 MPH

CONDITION IV




Figure 43

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .39
 RUDDER δ_R $3.8^\circ R$
 KICK DURATION T_1 1.5 Sec
 TIME TO APPLY ΔT_1 .2 Sec
 TIME TO RETURN ΔT_2 .2 Sec
 AILERON LOCKED

FLIGHT 33
 RUN 9138
 TIP TANKS OFF
 ALTITUDE 20,210 FT.
 O.A.T. $-17.4^\circ C$
 V_0 201 MPH




Figure 44

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .39

FLIGHT 33

RUDDER δ_R 3.8°R

RUN 9138

KICK DURATION T_1 1.5 SEC

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC

ALTITUDE 20,210 FT.

TIME TO RETURN ΔT_2 .2 SEC

O.A.T. -17.4°C

AILERON LOCKED

V_0 201 MPH

CONDITION IV




Figure 45

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69
 RUDDER δ_R 2.6%
 KICK DURATION T_1 1.1 SEC.
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC
 AILERON LOCKED

FLIGHT 34
 RUN 9220
 TIP TANKS OFF
 ALTITUDE 20,076 FT.
 O. A. T. -13.0 °C
 V_0 355.4 MPH

CONDITION V




Figure 46

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69

FLIGHT 34

RUDDER δ_R 2.6%

RUN 9220

KICK DURATION T_1 1.1 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,070 FT.

TIME TO RETURN ΔT_2 .2 SEC.

O. A. T. -13.0 °C.

AILERON LOCKED

V_0 355.4 MPH




Figure 47

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69
 RUDDER δ_R 2.6°
 KICK DURATION T_1 1.1 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 34
 RUN 9220
 TIP TANKS OFF
 ALTITUDE 30,074 FT.
 O. A. T. -13.0 °C
 V_0 355.4 MPH

CONDITION V




Figure 48

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69

FLIGHT 35

RUDDER δ_R 4.0°

RUN 9320

KICK DURATION T_1 1.0 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,170 FT


TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -11.4°C

AILERON LOCKED

V_0 351.8 MPH

CONDITION V



t - SEC.

Figure 49

- 85 -

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69

FLIGHT 35

RUDDER δ_R 4.0%

RUN 9320

KICK DURATION T_1 1.0 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,170 FT.




TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -11.2 °C

AILERON LOCKED

V_0 351.4 MPH

CONDITION II



t - SEC.
Figure 50

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69
 RUDDER δ_R 4.0°
 KICK DURATION T_1 1.0 SEC.
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC
 AILERON LOCKED

FLIGHT 35
 RUN 9320
 TIP TANKS OFF
 ALTITUDE 20,170 FT.
 O. A. T. -11.9 °C
 V_0 351.4 MPH

CONDITION V




Figure 51




F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69
 RUDDER δ_R 2.3°R
 KICK DURATION T_1 1.2 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 33
 RUN 9154
 TIP TANKS OFF
 ALTITUDE 20,060 FT.
 O.A.T. -17.3°C
 V_0 355.6 MPH

CONDITION V

ON



t - SEC.

Figure 52

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69

FLIGHT 33

RUDDER δ_R 2.5°

RUN 9154

KICK DURATION T_1 1.2 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,060 FT




TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -17.3°C

AILERON LOCKED

V_0 355.6 MPH.

CONDITION V



— R-SHEAR
- - - L-SHEAR

— R-BM
- - - L-BM

t - SEC.

Figure 53

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69

RUDDER δ_R 2.3°R

KICK DURATION T_1 1.2 SEC.

TIME TO APPLY ΔT_1 .2 SEC.

TIME TO RETURN ΔT_2 .2 SEC.

AILERON LOCKED

FLIGHT 33

RUN 9154

TIP TANKS OFF

ALTITUDE 29,060 FT.

O.A.T. -17.3 °C

V_0 355.6 MPH

CONDITION V




Figure 54

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69
 RUDDER δ_R 3.2°R
 KICK DURATION T_1 .9 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .1 SEC.
 AILERON LOCKED

FLIGHT 35
 RUN 9313
 TIP TANKS OFF
 ALTITUDE 20,010 FT.
 O.A.T. -11.6 °C
 V_0 357.7 MPH.

CONDITION V




Figure 55

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69

FLIGHT 35

RUDDER δ_R 3.2°

RUN 9313

KICK DURATION T_1 .9 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,010 FT.




TIME TO RETURN ΔT_2 .1 SEC.

O.A.T. -11.6°C

AILERON LOCKED

V_0 357.7 MPH

CONDITION V



t - SEC.

Figure 56

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .69

FLIGHT 35

RUDDER δ_R 3.2°R

RUN 9313

KICK DURATION T_1 .9 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,010 FT.

TIME TO RETURN ΔT_2 .1 SEC.

O. A. T. -11.6°C

AILERON LOCKED

V_0 357.7 MPH.

CONDITION V





Figure 57

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 4.6°
 KICK DURATION T_1 1.1 SEC.
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 38
 RUN 9742
 TIP TANKS EMPTY
 ALTITUDE 20,100 FT.
 O. A. T. -11.5°C
 V_0 303 MPH

CONDITION VI



1 - SEC.
 Figure 58

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

RUDDER δ_R 4.6%

KICK DURATION T_1 1.1 SEC.

TIME TO APPLY ΔT_1 .2 SEC.

TIME TO RETURN ΔT_2 .2 SEC

AILERON LOCKED

FLIGHT 38




RUN 9742

TIP TANKS EMPTY

ALTITUDE 20,100 FT.

O.A.T. -11.5°C

V_0 303 MPH



t - SEC.

Figure 59

F 80 A RUDDER KICK FLIGHT TESTS.

MACH NUMBER .59
 RUDDER δ_R 4.6°
 KICK DURATION T_1 1.1 SEC
 TIME TO APPLY ΔT_1 .25 SEC.
 TIME TO RETURN ΔT_2 .25 SEC.
 AILERON LOCKED

FLIGHT 38
 RUN 9742
 TIP TANKS EMPTY
 ALTITUDE 20,100 FT.
 O. A. T. -11.5°C
 V_0 303 MPH

CONDITION VI




Figure 60

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.0°
 KICK DURATION T_1 1.1 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 38
 RUN 9744
 TIP TANK EMPTY
 ALTITUDE 20,170 FT.
 O.A.T. -112 °C
 V_0 504 MPH

CONDITION VI




Figure 61

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 38

RUDDER δ_R 30°R

RUN 9744

KICK DURATION T_1 1.1 SEC

TIP TANKS EMPTY

TIME TO APPLY ΔT_1 .2 SEC

ALTITUDE 20,170 FT.

TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -11.2°C

AILERON LOCKED

V_0 304 MPH




Figure 62

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.0°R
 KICK DURATION T_1 1.1 SEC
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 38
 RUN 9744
 TIP TANKS EMPTY
 ALTITUDE 20,170 FT.
 O.A.T. -11.2°C
 V_0 304 MPH

CONDITION VI





Figure 63

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.4°
 KICK DURATION T_1 .8 SEC
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .1 SEC
 AILERON LOCKED

FLIGHT 38
 RUN 9747
 TIP TANKS EMPTY
 ALTITUDE 20,038 FT.
 O. A. T. -11.6°
 V_0 304.6 MPH

CONDITION VI



t - SEC.
Figure 64

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 38

RUDDER δ_R 3.4°

RUN 9747

KICK DURATION T_1 .8 SEC.

TIP TANKS EMPTY

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,038 FT.



TIME TO RETURN ΔT_2 .1 SEC.

O. A. T. -11.6°C


AILERON LOCKED

V_0 304.6 MPH

CONDITION VI



— RS
- - - LS



— RBM
- - - LBM

t - SEC.

Figure 65

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.4°R
 KICK DURATION T_1 .8 SEC
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .1 SEC
 AILERON LOCKED

FLIGHT 38
 RUN 9747
 TIP TANKS EMPTY
 ALTITUDE 20,038 FT.
 O.A.T. -11.6 °C
 V_0 304.6 MPH

CONDITION VI




Figure 66

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 38

RUDDER δ_R 3.4°R

RUN 9748

KICK DURATION T_1 1.5 SEC.

TIP TANKS EMPTY

TIME TO APPLY ΔT_1 .2 SEC

ALTITUDE 19,967 FT.


TIME TO RETURN ΔT_2 .2 SEC.

O. A. T. -11.2°C

AILERON LOCKED

V_0 303.7 MPH

CONDITION VI



t - SEC.
Figure 67

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 9.4°R
 KICK DURATION T_1 1.5 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 38
 RUN 9748
 TIP TANKS EMPTY
 ALTITUDE 19,967 FT.
 O.A.T. -112 °C
 V_0 303.7 MPH.




Figure 68

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.4°R
 KICK DURATION T_1 1.5 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON LOCKED

FLIGHT 38
 RUN 9748
 TIP TANKS EMPTY
 ALTITUDE 19,967 FT.
 O. A. T. -11.2 °C
 V_0 303.7 MPH

CONDITION VI




Figure 69

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 4.4%
 KICK DURATION T_1 1.1 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .1 SEC
 AILERON LOCKED

FLIGHT 38
 RUN 9759
 TIP TANKS HALF FULL
 ALTITUDE 20,130 FT.
 O. A. T. -11.2 °C
 V_0 303 MPH

CONDITION VII




Figure 70

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 38

RUDDER δ_R 4.4%

RUN 9739

KICK DURATION T_1 1.1 SEC

TIP TANKS HALF FULL

TIME TO APPLY ΔT_1 .2 SEC

ALTITUDE 20,130 FT

TIME TO RETURN ΔT_2 .1 SEC.

O. A. T. -11.2 °C

AILERON LOCKED

V_0 303 MPH




Figure 71

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 4.4%
 KICK DURATION T_1 1.1 SEC
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .1 SEC
 AILERON LOCKED

FLIGHT 38
 RUN 9739
 TIP TANKS HALF FULL
 ALTITUDE 20,130 FT.
 O. A. T. -11.2°C
 V_0 303 MPH

CONDITION VII




Figure 72

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .58

FLIGHT 38

RUDDER δ_R 3.5°R

RUN 9735

KICK DURATION T_1 1.3 SEC.

TIP TANKS HALF FULL

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 19,990 FT




TIME TO RETURN ΔT_2 .1 SEC.

O.A.T. -11.4°C

AILERON LOCKED

V_0 301.6 MPH

CONDITION VII



— FBM
- - - FS

t - SEC.



Figure 73

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .58
 RUDDER δ_R 3.5°
 KICK DURATION T_1 1.3 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .15 SEC.
 AILERON LOCKED

FLIGHT 38
 RUN 9735
 TIP TANKS HALF FULL
 ALTITUDE 19,990 FT.
 O. A. T. -11.4°C
 V_0 301.6 MPH

CONDITION VII



t - SEC.
Figure 74

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .58
 RUDDER δ_r 35°R
 KICK DURATION T_1 1.3 SEC.
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .1 SEC
 AILERON LOCKED

FLIGHT 38
 RUN 9735
 TIP TANKS HALF FULL
 ALTITUDE 19990 FT.
 O.A.T. -11.4°C
 V_0 301.6 MPH

CONDITION VII





Figure 75

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 3.8°
 KICK DURATION T_1 1.0 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .1 SEC.
 AILERON MOVED ANTI ROLL
 CONDITION VIII

FLIGHT 35
 RUN 9314
 TIP TANKS OFF
 ALTITUDE 19,970 FT.
 O.A.T. -12.2 °C
 V_0 304.1 MPH



t - SEC.

Figure 76

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 35

RUDDER δ_R 3.8°

RUN 9317

KICK DURATION T_1 1.0 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 19,970 FT.




TIME TO RETURN ΔT_2 .1 SEC.

O.A.T. -12.2 °C

AILERON MOVED ANTI ROLL

V_0 304.1 MPH

CONDITION VIII



t - SEC.

Figure 77

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 35

RUDDER δ_R 3.8°

RUN 9317

KICK DURATION T_1 1.0 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 19,970 FT.

TIME TO RETURN ΔT_2 .1 SEC.

O.A.T. -12.2°C

AILERON MOVED ANTI ROLL

V_0 304.1 MPH

CONDITION VIII




Figure 78

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R 5°
 KICK DURATION T_1 1.2 SEC.
 TIME TO APPLY ΔT_1 .2 SEC.
 TIME TO RETURN ΔT_2 .2 SEC.
 AILERON MOVED ANTI ROLL
 CONDITION VIII

FLIGHT 37
 RUN 9689
 TIP TANKS OFF
 ALTITUDE 20,195 FT.
 O.A.T. -11.1 °C
 V_0 303 MPH




Figure 79

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59
 RUDDER δ_R $5^\circ L$
 KICK DURATION T_1 1.2 SEC
 TIME TO APPLY ΔT_1 .2 SEC
 TIME TO RETURN ΔT_2 .2 SEC
 AILERON MOVED ANTI ROLL V_0 303 MPH

FLIGHT 37
 RUN 9689
 TIP TANKS OFF
 ALTITUDE 20,195 FT.
 O.A.T. $-11.1^\circ C$




Figure 80

F 80 A RUDDER KICK FLIGHT TESTS

MACH NUMBER .59

FLIGHT 37

RUDDER δ_R 5°

RUN 9689

KICK DURATION T_1 1.2 SEC.

TIP TANKS OFF

TIME TO APPLY ΔT_1 .2 SEC.

ALTITUDE 20,195 FT.


TIME TO RETURN ΔT_2 .2 SEC.

O.A.T. -11.1 °C

AILERON MOVED ANTI ROLL

V_0 303 MPH.

CONDITION VIII



t - SEC.
Figure 81

F - 80A STEADY SIDESLIP FLIGHT TESTS

MACH NUMBER .398

FLIGHTS 36 & 37

ALTITUDE 20225 FT.

O.A.T. -10.8°C

V_0 204.5 MPH

TIP TANKS OFF

CONDITION IX




Figure 82

F-80A STEADY SIDESLIP FLIGHT TESTS

MACH NUMBER .398

FLIGHTS 36 & 37


ALTITUDE 20225 FT.

O.A.T. -10.8°C.

V_e 204.5 MPH

TIP TANKS OFF

CONDITION IX



β ~ DEG.

Figure 83

- 129 -

F-80 A STEADY SIDESLIP FLIGHT TESTS

MACH NUMBER .588

FLIGHTS 36,37, & 38

ALTITUDE 20105 FT.

O. A. T. -11.4°C

V_e 302.5 MPH

CONDITION X




Figure 8h

F-80A STEADY SIDESLIP FLIGHT TESTS

MACH NUMBER .588


FLIGHTS 36, 37 & 38

ALTITUDE 20105 FT

O.A.T. -11.4°C

V_c 302.5 MPH

CONDITION X



F-80A STEADY SIDESLIP FLIGHT TESTS

MACH NUMBER .687

FLIGHTS 36 & 37

ALTITUDE 20075 FT.

O.A.T. -10.8°C

V_e 353.5 MPH

TIP TANKS OFF

CONDITION XI




Figure 86

F-80A STEADY SIDESLIP FLIGHT TESTS

MACH NUMBER .687

FLIGHTS 36 & 37

ALTITUDE 20075 FT.

O.A.T. -10.8°C.

V_e 353.5 MPH

TIP TANKS OFF

CONDITION XI




Figure 87